



# DURABLÜ

## PERFORMANCE STRENGTH OXFORD NYLON

MATERIAL PROPERTIES: Nylon 6.6, Polyurethane Coating

	SPECIFICATION	TOLERANCE	TEST METHOD
<b>Weight</b>	3.5 osy Nylon, 1 osy PU	+/- 10%	ASTM D3776
<b>Tensile Strength</b>	MD = 211 pounds CD = 180 pounds	+/- 10% +/- 10%	ASTM 5035 ASTM 5035
<b>Tear Strength</b>	MD = 40 pounds CD = 54 pounds	+/- 10% +/- 10%	ASTM D5134 ASTM D5134

Roll width: 92" | Roll length: 100yds | Roll diameter: 9" | Film: 3 mil Poly Bag | Core: 2" Cardboard

✦ IDEAL SOLUTION FOR DORMITORY AND HEALTHCARE ENVIORNMENT

✦ CFR1633 COMPLIANT WHEN LAMINATED TO A PRECISION FR BARRIER

✦ FLUID PROOF

✦ SHIELDS AGAINST STAINS, MOISTURE, MOLD & MILDEW

✦ ENHANCED DURABILITY AND EASY-CARE

✦ LEAD & PHTHALATE-FREE

✦ FULL OR SLIT ROLLS AVAILABLE



# PRECISION

## TEXTILES