

ADVANTAGE

TERRAFIRMA

	SPECIFICATION	TOLERANCE	TEST METHOD
Material Properties			
FIBER BLEND	Polyester Fiber with Tributyl Citrate Coating		
Physical Properties			
WEIGHT	4.2 osy	+/- 10%	ASTM D3776
THICKNESS	0.025 inches	+/- 10%	ASTM D5729
TENSILE STRENGTH	MD 30 pounds	+/- 10%	ASTM D5035
	CD 25 pounds	+/- 10%	ASTM D5035
TEAR STRENGTH	MD 5 pounds	+/- 10%	ASTM D2261
	CD 5 pounds	+/- 10%	ASTM D2261
ELONGATION	MD = 15%		ASTM D5035
	CD = 40%		ASTM D5035
Geometric Properties			
ROLL WIDTH	82 inches		
ROLL LENGTH	100 yards		
Packaging			
FILM CORE	3 mil poly bag 2 inch cardboard		

✦ HIGH-STRENGTH NON-FR STITCHBOND POLYESTER FILLER CLOTH WITH ENHANCED NON-SKID DOT COATING
DESIGNED TO HELP REDUCE MATTRESS MOVEMENT AND SLIPPING

✦ EASY-SEW CONSTRUCTION WITH NO BUILDUP ON SEWING NEEDLES, HELPING IMPROVE EFFICIENCY AND
REDUCE WASTE DURING MANUFACTURING

✦ DURABLE SKID-RESISTANT SURFACE AVAILABLE IN 82" WIDE ROLLS OR CUT-TO-SIZE PANELS FOR EFFICIENT
HANDLING ON THE PRODUCTION FLOOR

