

ADVANTAGE

PREMIUM QUALITY EASY-SEW NONWOVENS

| | SPECIFICATION | TOLERANCE | TEST METHOD |
|-----------------------------------------------------------|--------------------------------------------------------------------------|-----------|-------------|
| Material Properties | | | |
| FIBER BLEND | Polypropylene Spun Bond | | |
| Physical Properties | | | |
| WEIGHT | 0.50 – 2.25osy | +/- 10% | ASTM D3776 |
| THICKNESS | 0.020 - 0.08 inches | +/- 10% | ASTM D5729 |
| Aesthetics | | | |
| COLOR | White/ Black | | |
| Geometric Properties (Customer Specified) | | | |
| ROLL WIDTH ROLL LENGTH ROLL DIAMETER ROLL WEIGHT | 94 inches 500 yards 12 inches 82 pounds | | |
| Packaging | | | |
| FILM CORE QUANTITY/LABEL | 3 mil poly bag 2 inch cardboard 1 Roll per Bag/ Style, Lot, Roll # | | |

❖ SPUNBOND NONWOVENS AVAILABLE IN MULTIPLE WEIGHTS FOR USE ACROSS KEY MATTRESS COMPONENTS, INCLUDING DUST COVERS, FILLER CLOTH, FLANGES, AND INNER DECKING

❖ HIGH STRENGTH, LOW NOISE CONSTRUCTION DESIGNED FOR CLEAN CUTTING, EASY SEWING, AND DURABLE PERFORMANCE IN FINISHED BUILDS

❖ AVAILABLE IN A RANGE OF WEIGHTS TAILORED TO SPECIFIC APPLICATIONS, WITH PERFORATED ROLL OPTIONS TO SIMPLIFY HANDLING AND REDUCE CUTTING TIME ON THE PRODUCTION FLOOR

