

ECOLOFT

HIGHLOFT QUILT FILL

	SPECIFICATION	TOLERANCE	TEST METHOD
Material Properties			
Fiber Blend	Pillow Fill Polyester Bicomponent Polyester	+/- 5% +/- 5%	ASTM D629-99 ASTM D629-99
Physical Properties			
Weight Thickness	1.0 osf 1.8 inches	+/- 10% +/- 10%	ASTM D3776 ASTM D5729
Geometric Properties			
Roll Width Roll Length Roll Weight	88 inches 50 yards 69 pounds		
Packaging			
Film Core	4 mil Double Poly bag 2 inch cardboard		

- ✦ ADDS DEPTH, DIMENSION, AND IMPROVED BREATHABILITY TO QUILTED MATTRESS PANELS COMPARED TO TRADITIONAL POLYURETHANE FOAM
- ✦ SPIRAL CRIMPED POLYESTER PROVIDES RESILIENT LOFT, LONG-LASTING PERFORMANCE, AND DOES NOT PROMOTE BACTERIAL GROWTH
- ✦ HELPS REDUCE THE AMOUNT OF POLYURETHANE FOAM USED IN THE QUILT PACKAGE WHILE OFFERING A RECYCLABLE, NON-ALLERGENIC ALTERNATIVE

