VERDi-MED

REINFORCED INSTITUTIONAL VINYL FABRIC

MATERIAL PROPERTIES: 3 Ply Green Vinyl 18x12 300Dx500D PET Scrim

	SPECIFICATION	TOLERANCE	TEST METHOD
Weight	8.5 osy	+/- 10%	ASTM D3776
Tensile Strength	MD = 80 pounds	+/- 10%	ASTM D5035
	CD = 75 pounds	+/- 10%	ASTM D5035
Tear Strength	MD = 30 pounds	+/- 10%	ASTM D5587
	CD = 35 pounds	+/- 10%	ASTM D5587

	SPECIFICATION	TOLERANCE	TEST METHOD
Weight	10 osy	+/- 10%	ASTM D3776
Tensile Strength	MD =105 pounds	+/- 10%	ASTM D5035
	CD = 100 pounds	+/- 10%	ASTM D5035
Tear Strength	MD = 38 pounds	+/- 10%	ASTM D5587
	CD = 37 pounds	+/- 10%	ASTM D5587

Roll width: 82" | Roll length: 100yds | Roll diameter: 9" | Core: 2" Cardboard

- **HIGH-STRENGTH 3-PLY REINFORCED VINYL FABRIC DESIGNED FOR HEALTHCARE, INSTITUTIONAL, AND HIGH-USE MATTRESS APPLICATIONS**
- **FLUID-PROOF, ANTIMICROBIAL SURFACE HELPING PROTECT AGAINST STAINS, MOISTURE, MOLD, AND MILDEW WHILE REMAINING EASY TO CLEAN AND MAINTAIN**
- **AVAILABLE WITH INTEGRATED FR BARRIER LAMINATION AND SLIT-TO-WIDTH ROLL OPTIONS FOR CUT-AND-SEW OPTIMIZATION**

NFPA 701 FLAME RESISTANT

COMPLIANT PROPOSITION 65

QUALITY AWARD 2015 WINNER Johnson Controls EXCELLENCE IN EXECUTION

COMPLIANT CFR 1633